

FAG 32221-XL 参数

尺寸	d	105	mm	-	
	D	190	mm	-	
	T	53	mm	-	
	a	44.5	mm	-	
	B	50	mm	-	
	C	43	mm	-	
	C <sub>a min</sub>	5	mm	-	
	C <sub>b min</sub>	10	mm	-	
	D <sub>a max</sub>	178	mm	-	
	D <sub>a min</sub>	161	mm	-	
	D <sub>b min</sub>	180	mm	-	
	d <sub>1</sub>	143.6	mm	-	
	d <sub>a max</sub>	120	mm	-	
	d <sub>b min</sub>	117	mm	-	
	r <sub>1, 2 min</sub>	3	mm	-	
	r <sub>3, 4 min</sub>	2.5	mm	-	
	r <sub>a max</sub>	3	mm	-	
	r <sub>b max</sub>	2.5	mm	-	
	重量	m	6300	g	质量
	基本额定载荷	C <sub>r</sub>	455000	N	基本额定动载荷, 径向
C <sub>0r</sub>		550000	N	基本额定静载荷, 径向	
计算系数	e	0.42		-	
	Y	1.43		-	
	Y <sub>0</sub>	0.79		-	
疲劳极限载荷	C <sub>ur</sub>	79000	N	疲劳极限载荷, 径向	
极限转速	n <sub>G</sub>	3650	r/min	极限转速	
参考转速	n <sub>B</sub>	2490	r/min	参考速度	

FAG 32221-XL图片

