

FAG 33215参数

尺寸	a	32	mm	-	
	B	41	mm	-	
	C	31	mm	-	
	$C_{a \min}$	7	mm	-	
	$C_{b \min}$	10	mm	-	
	$D_{a \max}$	121	mm	-	
	$D_{a \min}$	111	mm	-	
	$D_{b \min}$	125	mm	-	
	d_1	104.5	mm	-	
	$d_{a \max}$	83	mm	-	
	$d_{b \min}$	84	mm	-	
	$r_{1, 2 \min}$	2	mm	-	
	$r_{3, 4 \min}$	1.5	mm	-	
	$r_{a \max}$	2	mm	-	
	$r_{b \max}$	1.5	mm	-	
	重量	m	2470	g	质量
	基本额定载荷	C_r	206000	N	基本额定动载荷, 径向
		C_{0r}	310000	N	基本额定静载荷, 径向
	计算系数	e	0.43		-
Y		1.4		-	
Y_0		0.77		-	
疲劳极限载荷	C_{ur}	39000	N	疲劳极限载荷, 径向	
极限转速	n_G	5200	r/min	极限转速	
参考转速	n_B	3350	r/min	参考速度	
说明		T3EE075		根据 DIN ISO 355 的 对应型号	
尺寸	d	75	mm	-	
	D	130	mm	-	

FAG 33215图片

