

FAG 241/630-B-K30-MB + AH241/630参数

重量	m	1360000	g	质量
	m_1	132000	g	质量, 退卸套
基本额定载荷	C_r	12900000	N	基本额定动载荷, 径向
计算系数	e	0.38		-
	Y_1	1.78		-
	Y_2	2.65		-
基本额定载荷	C_{0r}	29000000	N	基本额定静载荷, 径向
计算系数	Y_0	1.74		-
极限转速	n_G	440	r/min	极限转速
参考转速	n_B	136	r/min	参考速度
疲劳极限载荷	C_{ur}	1960000	N	疲劳极限载荷, 径向
尺寸	d_{1H}	600	mm	-
	D	1030	mm	-
	B	400	mm	-
	a	30	mm	-
	b	50	mm	-
	D_1	872.2	mm	-
	$D_{a \max}$	998	mm	-
	d	630	mm	-
	d_{2G}	Tr655x6		-
	$d_{a \min}$	662	mm	-
	d_s	12.5	mm	-
	l	450	mm	-
	n_s	23.5	mm	-
	$r_{a \max}$	6	mm	-
	r_{\min}	7.5	mm	-
说明		AH241/630		型号, 退卸套

FAG 241/630-B-K30-MB + AH241/630图片



参考资料:<http://www.sozhou.com/p/a6035f7d.html>