

FAG 32306-A参数

说明		T2FD030		根据 DIN ISO 355 的 对应型号	
尺寸	d	30	mm	-	
	D	72	mm	-	
	T	28.75	mm	-	
	a	18	mm	-	
	B	27	mm	-	
	C	23	mm	-	
	$C_a \text{ min}$	4	mm	-	
	$C_b \text{ min}$	5.5	mm	-	
	$D_a \text{ max}$	65	mm	-	
	$D_a \text{ min}$	59	mm	-	
	$D_b \text{ min}$	66	mm	-	
	d_1	49.3	mm	-	
	$d_a \text{ max}$	39	mm	-	
	$d_b \text{ min}$	37	mm	-	
	$r_{1, 2} \text{ min}$	1.5	mm	-	
	$r_{3, 4} \text{ min}$	1.5	mm	-	
	$r_a \text{ max}$	1.5	mm	-	
	$r_b \text{ max}$	1.5	mm	-	
	重量	m	587	g	质量
	基本额定载荷	C_r	80000	N	基本额定动载荷, 径向
C_{0r}		89000	N	基本额定静载荷, 径向	
计算系数	e	0.31		-	
	Y	1.9		-	
	Y_0	1.05		-	
疲劳极限载荷	C_{ur}	10800	N	疲劳极限载荷, 径向	
极限转速	n_G	10700	r/min	极限转速	

FAG 32306-A图片

