

### FAG 23136-E1-K-TVPB参数

尺寸	d	180	mm	-
	D	300	mm	-
	B	96	mm	-
	D <sub>1</sub>	264.8	mm	-
	D <sub>a max</sub>	286	mm	-
	d <sub>2</sub>	204.1	mm	-
	d <sub>a min</sub>	194	mm	-
	d <sub>s</sub>	8	mm	-
	n <sub>s</sub>	15	mm	-
	r <sub>a max</sub>	2.5	mm	-
	r <sub>min</sub>	3	mm	-
	重量	m	25900	g
基本额定载荷	C <sub>r</sub>	1420000	N	基本额定动载荷，径向
计算系数	e	0.29		-
	Y <sub>1</sub>	2.32		-
	Y <sub>2</sub>	3.45		-
基本额定载荷	C <sub>0r</sub>	1950000	N	基本额定静载荷，径向
计算系数	Y <sub>0</sub>	2.26		-
极限转速	n <sub>G</sub>	2230	r/min	极限转速
参考转速	n <sub>B</sub>	1370	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	195000	N	疲劳极限载荷，径向

### FAG 23136-E1-K-TVPB图片



参考资料:<http://www.sozhou.com/p/aa96c0a6.html>