

FAG 22216-E1-K + AH316参数

尺寸	d_{1H}	75	mm	-
	D	140	mm	-
	B	33	mm	-
	a	4	mm	-
	b	8	mm	-
	D_1	126.8	mm	-
	$D_{a \max}$	129	mm	-
	d	80	mm	-
	d_2	94.9	mm	-
	d_{2G}	M90x2		-
	$d_{a \min}$	91	mm	-
	d_s	3.2	mm	-
	l	48	mm	-
	n_s	6.5	mm	-
	$r_{a \max}$	2	mm	-
	r_{\min}	2	mm	-
说明		AH316		型号, 退卸套
重量	m	2080	g	质量
	m_1	380	g	质量, 退卸套
基本额定载荷	C_r	250000	N	基本额定动载荷, 径向
尺寸	e	0.22		-
计算系数	Y_1	3.14		-
	Y_2	4.67		-
基本额定载荷	C_{0r}	270000	N	基本额定静载荷, 径向
计算系数	Y_0	3.07		-
极限转速	n_G	6200	r/min	极限转速
参考转速	n_B	3700	r/min	参考速度
疲劳极限载荷	C_{ur}	33500	N	疲劳极限载荷, 径向

FAG 22216-E1-K + AH316图片



参考资料:<http://www.sozhou.com/p/b8136972.html>