

## NSK NUP2316参数

|        |      |          |       |      |
|--------|------|----------|-------|------|
| 型号     | 型号   | NUP2316  |       | -    |
| 外形尺寸   | SD   | 80       | mm    | 内径   |
|        | D    | 170      | mm    | 外径   |
|        | B    | 58       | mm    | 宽度   |
|        | R    | 2.1      | mm    | (最小) |
|        | R1   | 2.1      | mm    | (最小) |
|        | FW   | 103.0    | mm    | -    |
|        | EW   | 0.0      | mm    | -    |
| 基本额定载荷 | CR1  | 274000   | N     | 动载荷  |
|        | COR1 | 330000   | N     | 静载荷  |
|        | CR2  | 27900    | kgf   | 动载荷  |
|        | COR2 | 34000    | kgf   | 静载荷  |
| 极限转速   | LG   | 3200     | 1/min | 脂润滑  |
|        | LO   | 4000     | 1/min | 油润滑  |
| 安装尺寸   | DA1  | 91.0     | mm    | (最小) |
|        | DBB1 | 91.00000 | mm    | (最小) |
|        | DBB2 | 100      | mm    | (最大) |
|        | DC   | 105      | mm    | (最小) |
|        | DD1  | 114      | mm    | (最小) |
|        | DA2  | 159.0    | mm    | (最大) |
|        | DB1  | 0.0      | mm    | (最小) |
|        | DB2  | 0.0      | mm    | (最小) |
|        | RA   | 2.0      | mm    | (最大) |
|        | RB   | 2.0      | mm    | (最大) |
| 重量     | MASS | 5900     | g     | 重量   |

## NSK NUP2316图片

参考资料:<http://www.sozhou.com/p/babba427.html>

