

INA GE220-AW参数

|        |                     |          |       |               |
|--------|---------------------|----------|-------|---------------|
| 尺寸     | B                   | 82       | mm    | 公差: 0 / -0,6  |
|        | C                   | 67       | mm    | 公差: 0 / -0,6  |
|        | D <sub>1</sub>      | 265      | mm    | -             |
|        | D <sub>a min</sub>  | 279      | mm    | -             |
|        | d <sub>2</sub>      | 350      | mm    | -             |
|        | d <sub>3</sub>      | 289      | mm    | -             |
|        | d <sub>a max</sub>  | 289      | mm    | -             |
|        | d <sub>K</sub>      | 388      | mm    | -             |
|        | r <sub>1s min</sub> | 1.5      | mm    | 倒角尺寸          |
|        | r <sub>2s min</sub> | 0.6      | mm    | 倒角尺寸          |
|        | s                   | 75       | mm    | -             |
|        | 接触角                 | α        | 7     | -             |
|        | 重量                  | m        | 44700 | g             |
| 基本额定载荷 | C <sub>a</sub>      | 8530000  | N     | 基本额定动载荷, 轴向   |
|        | C <sub>0a</sub>     | 14220000 | N     | 基本额定静载荷, 轴向   |
| 尺寸     | d                   | 220      | mm    | 公差: 0 / -0,03 |
|        | D                   | 370      | mm    | 公差: 0 / -0,04 |
|        | T                   | 97       | mm    | 公差: 0 / -0,6  |

INA GE220-AW图片



