

NACHI 63/32N参数

| | | | | |
|-----------|----------|---------|-------|------|
| 外形尺寸 | d | 32 | mm | 内径 |
| | D | 75 | mm | 外径 |
| | B | 20 | mm | 宽度 |
| | r | 1.1~2 | mm | 轴向 |
| | r | 1.1~3.5 | mm | 轴向 |
| | r1 | 0.5~ | mm | 径向 |
| | r1 | 0.5~ | mm | 径向 |
| 止动槽和止动环尺寸 | D1 | 71.83 | mm | (最大) |
| | a | 3.28 | mm | (最大) |
| | b | 1.9 | mm | (最小) |
| | D2 | 81.6 | mm | (最大) |
| | f | 1.7 | mm | (最大) |
| 安装尺寸 | da (min) | 39 | mm | (最小) |
| | Da (max) | 68 | mm | (最大) |
| | Dx (min) | 83 | mm | (最小) |
| | ra (max) | 1 | mm | (最大) |
| | Cy (max) | 4.6 | mm | (最大) |
| 基本额定载荷 | Cr | 30000 | N | 动载荷 |
| | Cor | 16200 | N | 静载荷 |
| 极限速度 | Grease | 9500 | r/min | 脂润滑 |
| | Oil | 11000 | r/min | 油润滑 |

NACHI 63/32N图片

参考资料:<http://www.sozhou.com/p/bc7c1efe.html>

