

FAG 31308-A参数

尺寸	D	90	mm	-	
	T	25.25	mm	-	
	a	30	mm	-	
	B	23	mm	-	
	C	17	mm	-	
	$C_{a \min}$	4	mm	-	
	$C_{b \min}$	8	mm	-	
	$D_{a \max}$	81	mm	-	
	$D_{a \min}$	71	mm	-	
	$D_{b \min}$	86	mm	-	
	d_1	68.2	mm	-	
	$d_{a \max}$	51	mm	-	
	$d_{b \min}$	49	mm	-	
	$r_{1, 2 \min}$	2	mm	-	
	$r_{3, 4 \min}$	1.5	mm	-	
	$r_{a \max}$	2	mm	-	
	$r_{b \max}$	1.5	mm	-	
	重量	m	727	g	质量
	基本额定载荷	C_r	76000	N	基本额定动载荷，径向
C_{0r}		83000	N	基本额定静载荷，径向	
计算系数	e	0.83		-	
	Y	0.73		-	
	Y_0	0.4		-	
疲劳极限载荷	C_{ur}	9500	N	疲劳极限载荷，径向	
极限转速	n_G	8000	r/min	极限转速	
参考转速	n_B	5200	r/min	参考速度	
说明		T7FB040		根据 DIN ISO 355 的 对应型号	

FAG 31308-A图片

