

### NACHI 53407U参数

|        |          |         |       |         |
|--------|----------|---------|-------|---------|
| 外形尺寸   | d        | 35      | mm    | 内径      |
|        | D        | 80      | mm    | 外径      |
|        | T3       | 34      | mm    | 宽度      |
|        | T4       | 37      | mm    | 宽度      |
|        | r        | 1.1~2.7 | mm    | 径向和轴向方向 |
| 尺寸     | d1(max)  | 80      | mm    | (最大)    |
|        | D1(min)  | 37      | mm    | (最小)    |
|        | D2       | 58      | mm    | -       |
|        | D3       | 85      | mm    | -       |
|        | S        | 10      | mm    | -       |
|        | R        | 64      | mm    | -       |
|        | A        | 23      | mm    | -       |
| 安装尺寸   | da(min)  | 62      | mm    | (最小)    |
|        | Da2(max) | 58      | mm    | (最大)    |
|        | ra(max)  | 1       | mm    | (最大)    |
| 重量     | Mass     | 950     | g     | 重量      |
| 基本额定载荷 | Ca       | 87000   | N     | 动载荷     |
|        | Coa      | 155000  | N     | 静载荷     |
| 极限速度   | Grease   | 1900    | r/min | 脂润滑     |
|        | Oil      | 2900    | r/min | 油润滑     |

### NACHI 53407U图片

参考资料:<http://www.sozhou.com/p/c4070c42.html>

