

FAG 23272-B-K-MB + AH3272G参数

计算系数	Y_1	1.78		-
	Y_2	2.65		-
基本额定载荷	C_{0r}	9150000	N	基本额定静载荷，径向
计算系数	Y_0	1.74		-
极限转速	n_G	930	r/min	极限转速
参考转速	n_B	430	r/min	参考速度
疲劳极限载荷	C_{ur}	720000	N	疲劳极限载荷，径向
尺寸	d_{1H}	340	mm	-
	D	650	mm	-
	B	232	mm	-
	a	9	mm	-
	b	40	mm	-
	D_1	548.3	mm	-
	$D_{a \max}$	624	mm	-
	d	360	mm	-
	d_{2G}	Tr380x5		-
	$d_{a \min}$	386	mm	-
	d_s	12.5	mm	-
	l	274	mm	-
	n_s	23.5	mm	-
	$r_{a \max}$	5	mm	-
	r_{\min}	6	mm	-
说明		AH3272G		型号，退卸套
重量	m	328000	g	质量
	m_1	37300	g	质量，退卸套
基本额定载荷	C_r	4900000	N	基本额定动载荷，径向
计算系数	e	0.38		-

FAG 23272-B-K-MB + AH3272G图片



参考资料:<http://www.sozhou.com/p/c5e6c8fe.html>