

### FAG 22224-E1-K参数

尺寸	d	120	mm	-
	D	215	mm	-
	B	58	mm	-
	D <sub>1</sub>	192	mm	-
	D <sub>a max</sub>	203	mm	-
	d <sub>2</sub>	141.8	mm	-
	d <sub>a min</sub>	132	mm	-
	d <sub>s</sub>	6.3	mm	-
	n <sub>s</sub>	12.2	mm	-
	r <sub>a max</sub>	2.1	mm	-
	r <sub>min</sub>	2.1	mm	-
	重量	m	8840	g
基本额定载荷	C <sub>r</sub>	640000	N	基本额定动载荷，径向
尺寸	e	0.25		-
计算系数	Y <sub>1</sub>	2.71		-
	Y <sub>2</sub>	4.04		-
基本额定载荷	C <sub>0r</sub>	740000	N	基本额定静载荷，径向
计算系数	Y <sub>0</sub>	2.65		-
极限转速	n <sub>G</sub>	3650	r/min	极限转速
参考转速	n <sub>B</sub>	2800	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	71000	N	疲劳极限载荷，径向

### FAG 22224-E1-K图片



参考资料:<http://www.sozhou.com/p/c88052e6.html>