

### FAG 293/500-E-MB参数

尺寸	d	500	mm	-
	D	750	mm	-
	T	150	mm	-
	A	280	mm	-
	D <sub>1</sub>	610	mm	-
	D <sub>a max</sub>	683	mm	-
	D <sub>b min</sub>	768	mm	-
	d <sub>1</sub>	700	mm	-
	d <sub>a min</sub>	615	mm	-
	d <sub>b max</sub>	532	mm	-
	r <sub>a max</sub>	5	mm	-
	r <sub>min</sub>	6	mm	-
	T <sub>1</sub>	74	mm	-
	T <sub>2</sub>	54	mm	-
	T <sub>3</sub>	92	mm	-
	T <sub>4</sub>	105	mm	-
重量	m	212900	g	质量
基本额定载荷	C <sub>a</sub>	5100000	N	基本额定动载荷, 轴向
	C <sub>0a</sub>	22400000	N	基本额定静载荷, 轴向
极限转速	n <sub>G</sub>	690	r/min	极限转速
参考转速	n <sub>B</sub>	405	r/min	参考速度
疲劳极限载荷	C <sub>ua</sub>	1150000	N	疲劳极限载荷, 轴向

### FAG 293/500-E-MB图片



参考资料:<http://www.sozhou.com/p/c8bee761.html>