

FAG 30309-A参数

尺寸	d	45	mm	-	
	D	100	mm	-	
	T	27.25	mm	-	
	a	21	mm	-	
	B	25	mm	-	
	C	22	mm	-	
	$C_a \text{ min}$	3	mm	-	
	$C_b \text{ min}$	5	mm	-	
	$D_a \text{ max}$	91	mm	-	
	$D_a \text{ min}$	86	mm	-	
	$D_b \text{ min}$	92	mm	-	
	$d_1$	70.7	mm	-	
	$d_a \text{ max}$	59	mm	-	
	$d_b \text{ min}$	54	mm	-	
	$r_{1, 2} \text{ min}$	2	mm	-	
	$r_{3, 4} \text{ min}$	1.5	mm	-	
	$r_a \text{ max}$	2	mm	-	
	$r_b \text{ max}$	1.5	mm	-	
	重量	m	997	g	质量
	说明		T2FB045		根据 DIN ISO 355 的 对应型号
极限转速	$n_G$	7600	r/min	极限转速	
参考转速	$n_B$	5200	r/min	参考速度	
基本额定载荷	$C_r$	111000	N	基本额定动载荷, 径向	
	$C_{0r}$	125000	N	基本额定静载荷, 径向	
计算系数	e	0.35		-	
	Y	1.74		-	
	$Y_0$	0.96		-	

FAG 30309-A图片

