

FAG 240/850-B-K30-MB + AH240/850参数

尺寸	d_{1H}	800	mm	-
	D	1220	mm	-
	B	365	mm	-
	a	40	mm	-
	b	53	mm	-
	D_1	1092.9	mm	-
	$D_{a\ max}$	1192	mm	-
	d	850	mm	-
	d_{2G}	Tr880x7		-
	$d_{a\ min}$	878	mm	-
	d_s	12.5	mm	-
	l	418	mm	-
	n_s	23.5	mm	-
	$r_{a\ max}$	6	mm	-
	r_{min}	7.5	mm	-
说明		AH240/850		型号, 退卸套
重量	m	1420000	g	质量
	m_1	250000	g	质量, 退卸套
基本额定载荷	C_r	12900000	N	基本额定动载荷, 径向
计算系数	e	0.29		-
	Y_1	2.33		-
	Y_2	3.47		-
基本额定载荷	C_{0r}	32000000	N	基本额定静载荷, 径向
计算系数	Y_0	2.28		-
极限转速	n_G	390	r/min	极限转速
参考转速	n_B	174	r/min	参考速度
疲劳极限载荷	C_{ur}	2060000	N	疲劳极限载荷, 径向

FAG 240/850-B-K30-MB + AH240/850图片



参考资料:<http://www.sozhou.com/p/cacd0f31.html>