

### FAG 21319-E1-TVPB参数

尺寸	d	95	mm	-
	D	200	mm	-
	B	45	mm	-
	D <sub>1</sub>	169.4	mm	-
	D <sub>a max</sub>	186	mm	-
	d <sub>2</sub>	124.3	mm	-
	d <sub>a min</sub>	109	mm	-
	d <sub>s</sub>	4.8	mm	-
	n <sub>s</sub>	9.5	mm	-
	r <sub>a max</sub>	2.5	mm	-
	r <sub>min</sub>	3	mm	-
	重量	m	6630	g
基本额定载荷	C <sub>r</sub>	430000	N	基本额定动载荷，径向
计算系数	e	0.22		-
	Y <sub>1</sub>	3.04		-
	Y <sub>2</sub>	4.53		-
基本额定载荷	C <sub>0r</sub>	460000	N	基本额定静载荷，径向
计算系数	Y <sub>0</sub>	2.97		-
极限转速	n <sub>G</sub>	4550	r/min	极限转速
参考转速	n <sub>B</sub>	3300	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	47500	N	疲劳极限载荷，径向

### FAG 21319-E1-TVPB图片



参考资料:<http://www.sozhou.com/p/ccd96093.html>