

### FAG B7209-C-T-P4S参数

|        |               |       |       |             |
|--------|---------------|-------|-------|-------------|
| 尺寸     | d             | 45    | mm    | -           |
|        | D             | 85    | mm    | -           |
|        | B             | 19    | mm    | -           |
|        | a             | 18    | mm    | -           |
|        | $D_a$ H12     | 78    | mm    | -           |
|        | $d_a$ h12     | 52.5  | mm    | -           |
|        | $r_1$ min     | 1.1   | mm    | -           |
|        | $r_a$ max     | 1     | mm    | -           |
|        | $r_{al}$ max  | 1     | mm    | -           |
|        | $r_{min}$     | 1.1   | mm    | -           |
| 重量     | m             | 423   | g     | 质量          |
| 基本额定载荷 | $C_r$         | 34000 | N     | 基本额定动载荷, 径向 |
|        | $C_{0r}$      | 17700 | N     | 基本额定静载荷, 径向 |
| 极限转速   | $n_{G\ Fett}$ | 17000 | r/min | 脂润滑时的极限转速   |
|        | $n_{G\ Öl}$   | 28000 | r/min | 最少油润滑时的极限转速 |
| 疲劳极限载荷 | $C_{ur}$      | 1820  | N     | 疲劳极限载荷, 径向  |

### FAG B7209-C-T-P4S图片



