

FAG N1009-K-M1-SP参数

| | | | | |
|--------|--------------------|-------|-------|-------------|
| 尺寸 | d | 45 | mm | - |
| | D | 75 | mm | - |
| | B | 16 | mm | - |
| | $D_{a\ max}$ | 70 | mm | - |
| | $D_{b\ min}$ | 69 | mm | - |
| | d_1 | 55.4 | mm | - |
| | $d_{a\ min}$ | 48.2 | mm | - |
| | E | 67.5 | mm | - |
| | $r_{a\ max}$ | 1 | mm | - |
| | r_{min} | 1 | mm | - |
| | s | 1.5 | mm | 距离中心位置的轴向偏移 |
| 重量 | m | 268 | g | 质量 |
| 基本额定载荷 | C_r | 33500 | N | 基本额定动载荷, 径向 |
| | C_{0r} | 37500 | N | 基本额定静载荷, 径向 |
| 极限转速 | $n_{G\ Fett}$ | 15000 | r/min | 脂润滑时的极限转速 |
| | $n_{G\ \ddot{o}l}$ | 17000 | r/min | 最少油润滑时的极限转速 |
| 疲劳极限载荷 | C_{ur} | 5700 | N | 疲劳极限载荷, 径向 |

FAG N1009-K-M1-SP图片



