

### FAG 30236-A参数

参考转速	$n_B$	1500	r/min	参考速度	
说明		T4GB180		根据 DIN ISO 355 的 对应型号	
尺寸	d	180	mm	-	
	D	320	mm	-	
	T	57	mm	-	
	a	62	mm	-	
	B	52	mm	-	
	C	43	mm	-	
	$C_a \text{ min}$	9	mm	-	
	$C_b \text{ min}$	14	mm	-	
	$D_a \text{ max}$	302	mm	-	
	$D_a \text{ min}$	278	mm	-	
	$D_b \text{ min}$	297	mm	-	
	$d_1$	242	mm	-	
	$d_a \text{ max}$	211	mm	-	
	$d_b \text{ min}$	198	mm	-	
	$r_{1, 2} \text{ min}$	5	mm	-	
	$r_{3, 4} \text{ min}$	4	mm	-	
	$r_a \text{ max}$	5	mm	-	
	$r_b \text{ max}$	4	mm	-	
	重量	m	17900	g	质量
	基本额定载荷	$C_r$	610000	N	基本额定动载荷, 径向
$C_{0r}$		850000	N	基本额定静载荷, 径向	
计算系数	e	0.45		-	
	Y	1.33		-	
	$Y_0$	0.73		-	
疲劳极限载荷	$C_{ur}$	94000	N	疲劳极限载荷, 径向	

FAG 30236-A图片

