

FAG 32212-A参数

尺寸	B	28	mm	-	
	C	24	mm	-	
	$C_{a \min}$	4	mm	-	
	$C_{b \min}$	5.5	mm	-	
	$D_{a \max}$	101	mm	-	
	$D_{a \min}$	95	mm	-	
	$D_{b \min}$	104	mm	-	
	d_1	82.8	mm	-	
	$d_{a \max}$	69	mm	-	
	$d_{b \min}$	69	mm	-	
	$r_{1, 2 \min}$	2	mm	-	
	$r_{3, 4 \min}$	1.5	mm	-	
	$r_{a \max}$	2	mm	-	
	$r_{b \max}$	1.5	mm	-	
	重量	m	1180	g	质量
	基本额定载荷	C_r	133000	N	基本额定动载荷，径向
C_{0r}		169000	N	基本额定静载荷，径向	
计算系数	e	0.4		-	
	Y	1.48		-	
	Y_0	0.81		-	
疲劳极限载荷	C_{ur}	20600	N	疲劳极限载荷，径向	
极限转速	n_G	6600	r/min	极限转速	
参考转速	n_B	3800	r/min	参考速度	
说明		T3EC060		根据 DIN ISO 355 的 对应型号	
尺寸	d	60	mm	-	
	D	110	mm	-	
	T	29.75	mm	-	

FAG 32212-A图片

