

FAG 33207参数

尺寸	d	35	mm	-
	D	72	mm	-
	T	28	mm	-
	a	18	mm	-
	$d_{b \text{ min}}$	42	mm	-
	$r_{1, 2 \text{ min}}$	1.5	mm	-
	$r_{3, 4 \text{ min}}$	1.5	mm	-
	$r_{a \text{ max}}$	1.5	mm	-
	$r_{b \text{ max}}$	1.5	mm	-
	重量	m	585	g
基本额定载荷	C_r	86000	N	基本额定动载荷，径向
	C_{0r}	105000	N	基本额定静载荷，径向
计算系数	e	0.35		-
	Y	1.7		-
	Y_0	0.93		-
疲劳极限载荷	C_{ur}	12800	N	疲劳极限载荷，径向
极限转速	n_G	10100	r/min	极限转速
参考转速	n_B	6200	r/min	参考速度
说明		T2DE035		根据 DIN ISO 355 的 对应型号
尺寸	$D_{a \text{ max}}$	65	mm	-
	$D_{a \text{ min}}$	61	mm	-
	$D_{b \text{ min}}$	68	mm	-
	d_1	53	mm	-
	$d_{a \text{ max}}$	42	mm	-
	B	28	mm	-
	C	22	mm	-
	$C_{a \text{ min}}$	5	mm	-

FAG 33207图片

