

## FAG NJ406-M1 参数

|        |               |       |       |             |
|--------|---------------|-------|-------|-------------|
| 尺寸     | $D_{a\ max}$  | 79    | mm    | -           |
|        | $d_1$         | 50.3  | mm    | -           |
|        | $d_{a\ max}$  | 44    | mm    | -           |
|        | $d_{a\ min}$  | 41    | mm    | -           |
|        | $d_{c\ min}$  | 52    | mm    | -           |
|        | F             | 45    | mm    | -           |
|        | $r_{1\ min}$  | 1.5   | mm    | -           |
|        | $r_{a\ max}$  | 1.5   | mm    | -           |
|        | $r_{al\ max}$ | 1.5   | mm    | -           |
|        | $r_{min}$     | 1.5   | mm    | -           |
|        | s             | 2.3   | mm    | 距离中心位置的轴向偏移 |
| 重量     | m             | 872   | g     | 质量          |
| 基本额定载荷 | $C_r$         | 84000 | N     | 基本额定动载荷，径向  |
|        | $C_{0r}$      | 65000 | N     | 基本额定静载荷，径向  |
| 极限转速   | $n_G$         | 13400 | r/min | 极限转速        |
| 参考转速   | $n_B$         | 7900  | r/min | 参考速度        |
| 疲劳极限载荷 | $C_{ur}$      | 11000 | N     | 疲劳极限载荷，径向   |
| 尺寸     | d             | 30    | mm    | -           |
|        | D             | 90    | mm    | -           |
|        | B             | 23    | mm    | -           |
|        | $B_1$         | 7     | mm    | -           |
|        | $B_2$         | 11.5  | mm    | -           |
|        | $D_1$         | 68.4  | mm    | -           |

## FAG NJ406-M1 图片





参考资料:<http://www.sozhou.com/p/d816faa3.html>