

FAG 23160-B-K-MB + AH3160G参数

尺寸	d_{1H}	280	mm	-
	D	500	mm	-
	B	160	mm	-
	a	8	mm	-
	b	30	mm	-
	D_1	434.7	mm	-
	$D_{a\ max}$	480	mm	-
	d	300	mm	-
	d_{2G}	Tr320x5		-
	$d_{a\ min}$	320	mm	-
	d_s	9.5	mm	-
	l	192	mm	-
	n_s	17.7	mm	-
	$r_{a\ max}$	4	mm	-
	r_{min}	5	mm	-
	说明		AH3160G	
重量	m	123000	g	质量
	m_1	20000	g	质量, 退卸套
基本额定载荷	C_r	2650000	N	基本额定动载荷, 径向
计算系数	e	0.33		-
	Y_1	2.06		-
	Y_2	3.06		-
基本额定载荷	C_{0r}	4900000	N	基本额定静载荷, 径向
计算系数	Y_0	2.01		-
极限转速	n_G	1300	r/min	极限转速
参考转速	n_B	730	r/min	参考速度
疲劳极限载荷	C_{ur}	270000	N	疲劳极限载荷, 径向

FAG 23160-B-K-MB + AH3160G图片



参考资料:<http://www.sozhou.com/p/d9735dee.html>