

FAG 230/500-B-K-MB + AHX30/500参数

| | | | | |
|--------|--------------|-----------|-------|-------------|
| 尺寸 | d_{1H} | 480 | mm | - |
| | D | 720 | mm | - |
| | B | 167 | mm | - |
| | a | 12 | mm | - |
| | b | 40 | mm | - |
| | D_1 | 653.5 | mm | - |
| | $D_{a\ max}$ | 697 | mm | - |
| | d | 500 | mm | - |
| | d_{2G} | Tr540x6 | | - |
| | $d_{a\ min}$ | 523 | mm | - |
| | d_s | 12.5 | mm | - |
| | l | 209 | mm | - |
| | n_s | 23.5 | mm | - |
| | $r_{a\ max}$ | 5 | mm | - |
| | r_{min} | 6 | mm | - |
| 说明 | | AHX30/500 | | 型号, 退卸套 |
| 重量 | m | 219000 | g | 质量 |
| | m_1 | 42500 | g | 质量, 退卸套 |
| 基本额定载荷 | C_r | 3900000 | N | 基本额定动载荷, 径向 |
| 计算系数 | e | 0.22 | | - |
| | Y_1 | 3.01 | | - |
| | Y_2 | 4.48 | | - |
| 基本额定载荷 | C_{0r} | 8500000 | N | 基本额定静载荷, 径向 |
| 计算系数 | Y_0 | 2.94 | | - |
| 极限转速 | n_G | 890 | r/min | 极限转速 |
| 参考转速 | n_B | 520 | r/min | 参考速度 |
| 疲劳极限载荷 | C_{ur} | 510000 | N | 疲劳极限载荷, 径向 |

FAG 230/500-B-K-MB + AHX30/500图片



参考资料:<http://www.sozhou.com/p/dfa82e53.html>