

## FAG 30319-A参数

尺寸	$r_{3, 4 \text{ min}}$	3	mm	-
	$r_{a \text{ max}}$	4	mm	-
	$r_{b \text{ max}}$	3	mm	-
重量	m	6770	g	质量
基本额定载荷	$C_r$	360000	N	基本额定动载荷, 径向
	$C_{0r}$	440000	N	基本额定静载荷, 径向
计算系数	e	0.35		-
	Y	1.74		-
	$Y_0$	0.96		-
疲劳极限载荷	$C_{ur}$	47500	N	疲劳极限载荷, 径向
极限转速	$n_G$	3650	r/min	极限转速
参考转速	$n_B$	3000	r/min	参考速度
说明		T2GB095		根据 DIN ISO 355 的 对应型号
尺寸	d	95	mm	-
	D	200	mm	-
	T	49.5	mm	-
	a	40	mm	-
	B	45	mm	-
	C	38	mm	-
	$C_{a \text{ min}}$	6	mm	-
	$C_{b \text{ min}}$	11.5	mm	-
	$D_{a \text{ max}}$	186	mm	-
	$D_{a \text{ min}}$	172	mm	-
	$D_{b \text{ min}}$	184	mm	-
	$d_1$	139	mm	-
	$d_{a \text{ max}}$	118	mm	-
	$d_{b \text{ min}}$	109	mm	-

FAG 30319-A图片

