

### FAG NU317-E-TVP2参数

尺寸	d	85	mm	-
	D	180	mm	-
	B	41	mm	-
	D <sub>1</sub>	152.7	mm	-
	D <sub>a max</sub>	166	mm	-
	d <sub>a max</sub>	106	mm	-
	d <sub>a min</sub>	99	mm	-
	d <sub>b min</sub>	110	mm	-
	E	160	mm	-
	F	108	mm	-
	r <sub>l min</sub>	3	mm	-
	r <sub>a max</sub>	2.5	mm	-
	r <sub>al max</sub>	2.5	mm	-
	r <sub>min</sub>	3	mm	-
	s	1.3	mm	距离中心位置的轴向偏移
重量	m	4620	g	质量
基本额定载荷	C <sub>r</sub>	320000	N	基本额定动载荷，径向
	C <sub>0r</sub>	300000	N	基本额定静载荷，径向
极限转速	n <sub>G</sub>	4550	r/min	极限转速
参考转速	n <sub>B</sub>	4000	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	39500	N	疲劳极限载荷，径向

### FAG NU317-E-TVP2图片



参考资料:<http://www.sozhou.com/p/e1320c4b.html>

