

FAG 23268-B-K-MB + H3268参数

尺寸	r_{\min}	6	mm	-
说明		H3268		质量, 紧定套
重量	m	291000	g	质量
	m_1	55400	g	质量, 紧定套
基本额定载荷	C_r	4500000	N	基本额定动载荷, 径向
计算系数	e	0.38		-
	Y_1	1.78		-
	Y_2	2.65		-
基本额定载荷	C_{0r}	8150000	N	基本额定静载荷, 径向
计算系数	Y_0	1.74		-
极限转速	n_G	980	r/min	极限转速
参考转速	n_B	470	r/min	参考速度
疲劳极限载荷	C_{ur}	650000	N	疲劳极限载荷, 径向
尺寸	d_{1H}	320	mm	-
	D	620	mm	-
	B	224	mm	-
	$B_{a \min}$	14	mm	-
	c	55	mm	-
	c_1	70	mm	-
	D_1	521.2	mm	-
	$D_{a \max}$	594	mm	-
	D_m	440	mm	-
	d	340	mm	-
	$d_{a \max}$	402	mm	-
	$d_{b \min}$	364	mm	-
	d_s	12.5	mm	-
	l	288	mm	-

n_s	23.5	mm	-
$r_{a \max}$	5	mm	-

FAG 23268-B-K-MB + H3268图片

