

### FAG NU315-E-TVP2参数

尺寸	d	75	mm	-
	D	160	mm	-
	B	37	mm	-
	D <sub>1</sub>	136.2	mm	-
	D <sub>a max</sub>	148	mm	-
	d <sub>a max</sub>	93	mm	-
	d <sub>a min</sub>	87	mm	-
	d <sub>b min</sub>	97	mm	-
	E	143	mm	-
	F	95	mm	-
	r <sub>1 min</sub>	2.1	mm	-
	r <sub>a max</sub>	2.1	mm	-
	r <sub>al max</sub>	2.1	mm	-
	r <sub>min</sub>	2.1	mm	-
	s	1.2	mm	距离中心位置的轴向偏移
重量	m	3330	g	质量
基本额定载荷	C <sub>r</sub>	285000	N	基本额定动载荷，径向
	C <sub>0r</sub>	265000	N	基本额定静载荷，径向
极限转速	n <sub>G</sub>	5100	r/min	极限转速
参考转速	n <sub>B</sub>	4200	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	34500	N	疲劳极限载荷，径向

### FAG NU315-E-TVP2图片



参考资料:<http://www.sozhou.com/p/e93a7a96.html>

