

FAG 24172-B-K30 + AH24172参数

尺寸	D	600	mm	-
	B	243	mm	-
	a	20	mm	-
	b	26	mm	-
	D <sub>1</sub>	503.6	mm	-
	D <sub>a max</sub>	580	mm	-
	d	360	mm	-
	d <sub>2G</sub>	Tr380x5		-
	d <sub>a min</sub>	380	mm	-
	d <sub>s</sub>	9.5	mm	-
	l	269	mm	-
	n <sub>s</sub>	17.7	mm	-
	r <sub>a max</sub>	4	mm	-
	r <sub>min</sub>	5	mm	-
说明		AH24172		型号, 退卸套
尺寸	d <sub>1H</sub>	340	mm	-
重量	m	275000	g	质量
	m <sub>1</sub>	29700	g	质量, 退卸套
基本额定载荷	C <sub>r</sub>	4500000	N	基本额定动载荷, 径向
计算系数	e	0.41		-
	Y <sub>1</sub>	1.63		-
	Y <sub>2</sub>	2.43		-
基本额定载荷	C <sub>0r</sub>	9000000	N	基本额定静载荷, 径向
计算系数	Y <sub>0</sub>	1.6		-
极限转速	n <sub>G</sub>	880	r/min	极限转速
参考转速	n <sub>B</sub>	355	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	550000	N	疲劳极限载荷, 径向

FAG 24172-B-K30 + AH24172图片



参考资料:<http://www.sozhou.com/p/ef45ab6c.html>