

### FAG 32203-A参数

尺寸	d	17	mm	-	
	D	40	mm	-	
	T	17.25	mm	-	
	a	11	mm	-	
	B	16	mm	-	
	C	14	mm	-	
	C <sub>a min</sub>	3	mm	-	
	C <sub>b min</sub>	3	mm	-	
	D <sub>a max</sub>	34	mm	-	
	D <sub>a min</sub>	34	mm	-	
	D <sub>b min</sub>	37	mm	-	
	d <sub>1</sub>	28.7	mm	-	
	d <sub>a max</sub>	22	mm	-	
	d <sub>b min</sub>	23	mm	-	
	r <sub>1, 2 min</sub>	1	mm	-	
	r <sub>3, 4 min</sub>	1	mm	-	
	r <sub>a max</sub>	1	mm	-	
	r <sub>b max</sub>	1	mm	-	
	重量	m	105	g	质量
	基本额定载荷	C <sub>r</sub>	29000	N	基本额定动载荷，径向
C <sub>0r</sub>		29500	N	基本额定静载荷，径向	
计算系数	e	0.31		-	
	Y	1.92		-	
	Y <sub>0</sub>	1.06		-	
疲劳极限载荷	C <sub>ur</sub>	3300	N	疲劳极限载荷，径向	
极限转速	n <sub>G</sub>	19500	r/min	极限转速	
参考转速	n <sub>B</sub>	10800	r/min	参考速度	

FAG 32203-A图片

