

### FAG NJ310-E-TVP2参数

尺寸	d	50	mm	-
	D	110	mm	-
	B	27	mm	-
	B <sub>1</sub>	8	mm	-
	B <sub>2</sub>	13	mm	-
	D <sub>1</sub>	92.5	mm	-
	D <sub>a max</sub>	99	mm	-
	d <sub>1</sub>	71.3	mm	-
	d <sub>a max</sub>	63	mm	-
	d <sub>a min</sub>	61	mm	-
	d <sub>c min</sub>	73	mm	-
	F	65	mm	-
	r <sub>1 min</sub>	2	mm	-
	r <sub>a max</sub>	2	mm	-
	r <sub>a1 max</sub>	2	mm	-
	r <sub>min</sub>	2	mm	-
	s	1.7	mm	距离中心位置的轴向偏移
重量	m	1190	g	质量
基本额定载荷	C <sub>r</sub>	131000	N	基本额定动载荷，径向
	C <sub>0r</sub>	114000	N	基本额定静载荷，径向
极限转速	n <sub>G</sub>	7800	r/min	极限转速
参考转速	n <sub>B</sub>	6100	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	20100	N	疲劳极限载荷，径向

### FAG NJ310-E-TVP2图片





参考资料:<http://www.sozhou.com/p/f2cf05f1.html>