

FAG 24164-B-K30 + AH24164参数

尺寸	d_{1H}	300	mm	-
	D	540	mm	-
	B	218	mm	-
	a	18	mm	-
	b	24	mm	-
	D_1	456.1	mm	-
	$D_{a\ max}$	520	mm	-
	d	320	mm	-
	d_{2G}	Tr340x5		-
	$d_{a\ min}$	340	mm	-
	d_s	9.5	mm	-
	l	242	mm	-
	n_s	17.7	mm	-
	$r_{a\ max}$	4	mm	-
	r_{min}	5	mm	-
说明		AH24164		型号, 退卸套
重量	m	197000	g	质量
	m_1	23400	g	质量, 退卸套
基本额定载荷	C_r	3800000	N	基本额定动载荷, 径向
计算系数	e	0.41		-
	Y_1	1.65		-
	Y_2	2.46		-
基本额定载荷	C_{0r}	7350000	N	基本额定静载荷, 径向
计算系数	Y_0	1.61		-
极限转速	n_G	1010	r/min	极限转速
参考转速	n_B	415	r/min	参考速度
疲劳极限载荷	C_{ur}	530000	N	疲劳极限载荷, 径向

FAG 24164-B-K30 + AH24164图片



参考资料:<http://www.sozhou.com/p/f2eb7c2d.html>