

FAG 22260-K-MB + AH2260G参数

尺寸	$d_{a \min}$	320	mm	-
	$d_s$	12.5	mm	-
	$l$	170	mm	-
	$n_s$	23.5	mm	-
	$r_{a \max}$	4	mm	-
	$r_{\min}$	5	mm	-
说明		AH2260G		型号, 退卸套
重量	$m$	136000	g	质量
	$m_1$	17200	g	质量, 退卸套
基本额定载荷	$C_r$	2750000	N	基本额定动载荷, 径向
计算系数	$e$	0.27		-
	$Y_1$	2.47		-
	$Y_2$	3.67		-
基本额定载荷	$C_{0r}$	4400000	N	基本额定静载荷, 径向
计算系数	$Y_0$	2.41		-
极限转速	$n_G$	1490	r/min	极限转速
参考转速	$n_B$	900	r/min	参考速度
疲劳极限载荷	$C_{ur}$	300000	N	疲劳极限载荷, 径向
尺寸	$d_{1H}$	280	mm	-
	$D$	540	mm	-
	$B$	140	mm	-
	$a$	8	mm	-
	$b$	26	mm	-
	$D_1$	468.8	mm	-
	$D_{a \max}$	520	mm	-
	$d$	300	mm	-
	$d_{2G}$	Tr320x5		-

FAG 22260-K-MB + AH2260G图片



参考资料:<http://www.sozhou.com/p/f62ce144.html>