

### FAG NU2260-EX-TB-M1参数

尺寸	d	300	mm	-
	D	540	mm	-
	B	140	mm	-
	D <sub>1</sub>	467	mm	-
	D <sub>a max</sub>	520	mm	-
	d <sub>a max</sub>	352	mm	-
	d <sub>a min</sub>	320	mm	-
	d <sub>b min</sub>	358	mm	-
	E	495	mm	-
	F	355	mm	-
	r <sub>1 min</sub>	5	mm	-
	r <sub>a max</sub>	4	mm	-
	r <sub>al max</sub>	4	mm	-
	r <sub>min</sub>	5	mm	-
	s	12.2	mm	距离中心位置的轴向偏移
重量	m	143000	g	质量
基本额定载荷	C <sub>r</sub>	2700000	N	基本额定动载荷，径向
	C <sub>0r</sub>	4100000	N	基本额定静载荷，径向
极限转速	n <sub>G</sub>	1780	r/min	极限转速
参考转速	n <sub>B</sub>	660	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	410000	N	疲劳极限载荷，径向

### FAG NU2260-EX-TB-M1图片



参考资料:<http://www.sozhou.com/p/fad8053a.html>

