

FAG 23080-K-MB + AH3080G参数

尺寸	B	148	mm	-
	a	10	mm	-
	b	33	mm	-
	D ₁	540.5	mm	-
	D _{a max}	582	mm	-
	d	400	mm	-
	d _{2G}	Tr420x5		-
	d _{a min}	418	mm	-
	d _s	12.5	mm	-
	l	183	mm	-
	n _s	23.5	mm	-
	r _{a max}	4	mm	-
	r _{min}	5	mm	-
说明		AH3080G		型号, 退卸套
重量	m	143000	g	质量
	m ₁	25400	g	质量, 退卸套
基本额定载荷	C _r	3050000	N	基本额定动载荷, 径向
计算系数	e	0.24		-
	Y ₁	2.79		-
	Y ₂	4.15		-
基本额定载荷	C _{0r}	6200000	N	基本额定静载荷, 径向
计算系数	Y ₀	2.73		-
极限转速	n _G	1120	r/min	极限转速
参考转速	n _B	680	r/min	参考速度
疲劳极限载荷	C _{ur}	365000	N	疲劳极限载荷, 径向
尺寸	D	600	mm	-
	d _{1H}	380	mm	-

FAG 23080-K-MB + AH3080G图片



参考资料:<http://www.sozhou.com/p/fbb238ea.html>