


### FAG 29372-E1-MB参数

尺寸	T	122	mm	-
	A	202	mm	-
	D <sub>1</sub>	448	mm	-
	D <sub>a max</sub>	504	mm	-
	D <sub>b min</sub>	572	mm	-
	d <sub>1</sub>	520	mm	-
	d <sub>a min</sub>	455	mm	-
	d <sub>b max</sub>	385	mm	-
	r <sub>a max</sub>	4	mm	-
	r <sub>min</sub>	5	mm	-
	T <sub>1</sub>	59.5	mm	-
	T <sub>2</sub>	44	mm	-
	T <sub>3</sub>	75	mm	-
	T <sub>4</sub>	117	mm	-
	重量	m	105400	g
基本额定载荷	C <sub>a</sub>	3750000	N	基本额定动载荷, 轴向
	C <sub>0a</sub>	13000000	N	基本额定静载荷, 轴向
极限转速	n <sub>G</sub>	1110	r/min	极限转速
参考转速	n <sub>B</sub>	580	r/min	参考速度
疲劳极限载荷	C <sub>ua</sub>	1280000	N	疲劳极限载荷, 轴向
尺寸	d	360	mm	-
	D	560	mm	-

### FAG 29372-E1-MB图片



参考资料:<http://www.sozhou.com/p/ff10178b.html>